

Specifications Cordstrap Composite Strapping Solution: CC60 & CB6

Performance Specifications	
Performance System (strap & buckle) System Breaking Strength*	760 daN / 1710 lbf
Performance Strap Linear Breaking Strength* Elongation Elongation at Break	470 daN / 1055 lbf <7% 11% - 17%
Certification	German Lloyd



Strap Specifications	
Dimensions Width* Thickness*	19mm / 3/4" 0,85 mm / 1/32"
Material	High tenacity polyester filament yarn and Homopolymer Polypropylene
Coil Length per Coil** Core Diameter	600 m / 2000 ft 200 mm / 8"
Packaging Carton Box Dimensions* Box Weight* Product Code	2 coils per box 390 x 390 x 354 mm / 15.3/8" x 15.3/8" x 14" 19 kg / 42 lbs 7253000
Pallet Box Dimensions* Box Weight* Product Code	30 coils per box 1181 x 781 x 890 mm / 46.9" x 31.1" x 35" 291 kg / 642 lbs 7253900

Buckle Specifications	
Dimensions Width*	19 mm / 3/4"
Material	Galvanized steel wire
Packaging Carton Box** Dimensions* Box Weight* Product Code	500 pieces per box 266 x 166 x 272 mm / 10.1/2" x 6.5/8" x 8.5/8" 9 kg / 20 lbs 7354500



Represented in over 50 countries

World market leader
ISO 9001:2008 certified
Manufacturer & supplier since 1965
Offering genuine customer solutions

Specialist advice
Continued product development
Training at Cordstrap Training Centers
Quality assurance

Recommended Tensioner(s)	
Manual Tensioner Applied Pre-tension Suitable for strap widths Suitable for strap thicknesses Weight* Product Code	CT20 50 – 450 daN / 110 – 1010 lbf 13 mm - 19 mm / 1/2" - 3/4" 0, 4 - 1,2 mm / 11/64" - 3/64" 1,3 kg / 2.9 lbs 7500000
Manual Tensioner Applied Pre-tension Suitable for strap widths Suitable for strap thicknesses Weight* Product Code	CTT20 50 – 450 daN / 110 – 1010 lbf 13 mm - 19 mm / 1/2" - 3/4" 0,6 - 1,5 mm / 1/32" - 1/16" 1,2 kg / 2.6 lbs 7501000

Accessories	
Coil Dispenser with Buckle Tray Product Code Portable Version Product Code Static Version	7538000 7544000
Edge Protection	Different types and sizes available. Your Cordstrap cargo securing specialist can advise you about the best Edge Protection for your application.
Pallet Needle Product Code	7551000

* Tolerance of +/- 10%

** Tolerance of +/- 2%

We recommend storing all Cordstrap Products in a cool a dry environment out of direct sunlight and between -5°C and 40°C / 23°F and 104°F

All information provided is based on accuracy at time of creation



Represented in over 50 countries

World market leader

ISO 9001:2008 certified

Manufacturer & supplier since 1965

Offering genuine customer solutions

Specialist advice

Continued product development

Training at Cordstrap Training Centers

Quality assurance