



Stretch **Up to 260%** 

## FIBER FILM GAMMA-L Light Core


## **Product Overview**


Fiber Film is a novel, high efficiency stretch film with reinforcement elements (fibers) that increase tear resistance.

Fiber Film Gamma-L has revolutionary features offering:

- ► Compatibility with Advanced Wrapping Machines
- ► Replaces a stretch film of 17µm thickness or less
- ► Worry free performance: place it forget it!
- ► No breaks during wrapping process
- ► Exceptional load retention & stability

Technical Specifications							
		Tolerance					
Tensile strength at break (N/mm²)	23,5	10%					
Elongation at break (%)	375	10%					
Film width (mm)	485	2%					
Film weight (gr/m)	5,2	5%					





260%

total stretch should be adjusted accordingly

## Instructions for storage and use:

Total stretch, up to

The film should be stored in closed, dry and dust-free rooms, storage temperature 15-25°C with complementary conditions:

Protected against sunrays exposure and away from heat-emitting sources (heaters, radiators, hot air ventilators)

- -The film should be protected against humidity and dust
- -The film should be protected against mechanical damages
- -The film should be stored on the pallets. Direct contact with concrete or floor is not allowed
- -The temperature recommended by film producer for proper film parameters during application +15°C to +30°C

30 25						Ga nce				1
20 <b>Force</b> MPa 10 5										
0	)	50	100	150	200	250	300	350	400	450
Elongation, %										

Packaging Specifications	
Gross Roll Weight* (kg)	11,9
Film Length per roll** (m)	2100
Roll Diameter (O.D.)*** mm	228
Core diameter (mm)	76
Core Weight (kg)	1,0
Rolls per pallet	36
Net Pallet Weight *(kg)	428
Weight Tolerance*	±5%
Length Tolerance**	±2%
Roll diameter Tolerance***	±2%

Pallet dimensions: 80cm x 120cm x 115cm

Disclaimer: Data presented herein is based on internal tests. No liability, warranty or guarantee of product performance is created by this document.



